

## OMNITRONIC Set CMX-2000 + 2x DD-5220L

Set with digital DJ mixer/controller and two turntables

Art.n.: 20000395

GTIN:



**L'articolo non è più disponibile.**

### Features :

#### OMNITRONIC CMX-2000 2+1-channel MIDI controller

Digital DJ mixer and controller incl. Virtual DJ 7 LE

- 2-channel DJ mixer/MIDI controller bundled with Virtual DJ
- Optimized layout for Virtual DJ and Traktor PRO 2 - Virtual DJ 7 LE voucher included
- Traktor PRO 2 and Serato Scratch Live mappings available with full support for scratch and sample decks
- Flexibly combines stand-alone mixing of analog sources with MIDI control for DJ software
- Built-in DVS audio system for direct use of timecode systems with vinyl or CD in Virtual DJ and other open applications via USB
- 2 input channels with routing facility for analog inputs and MIDI decks as desired
- Full-fledged MIDI sections with 2 layers for 4-deck control
- Perfect MIDI control for file browsing, transportation, hot cues, samples, sample recorder, loops, effects, pitch and video transitions
- Advanced setup options for scratch DJs: crossfader and channel faders with adjustable curve and reverse selectors
- Built-in USB sound card 4 IN/4 OUT
- Supports Mac OSX, Windows XP, Vista, 7
- Professional-grade metal chassis with replaceable crossfader (45 mm)
- 2 line and 2 line/phono RCA inputs for connecting CD players, turntables and other external hardware
- 2 AUX inputs (3.5 mm/6.3 mm jack) connect MP3 players and tablets
- Mic input (XLR/6.3 mm jack) with tone control and talkover
- 2 master outputs (XLR/RCA) for PA applications
- Booth output (RCA), independently adjustable
- 3.5 mm/6.3 mm jack dual headphones output with cue mix control

### Logistica

- Bright color-coded LED buttons provide optimal visual feedback while triggering loops, samples, effects and cue points
- User-definable LED modes for Serato Scratch Live
- Dual-function audio/video crossfader for video performances within Virtual DJ
- 3-band EQ (high, mid, low) and HP/LP filter per channel
- Mixer section switchable between analog mode and MIDI mode
- File selector encoder and 2 load buttons for mouseless music library control
- 8 Hot Cue buttons per channel
- Auto Loop function with Beat Jump (Loop Cut), manual Loop In/Out buttons
- FX/sampler units with 4 parameter controls and 4 buttons per channel
- Various controls for GUI, mixer and video
- Shift button for various dual-button operations
- Separate VU meters for master and PFL signal
- Crossfader with faderstart function for compatible CD players
- Compatible to any MIDI-controlled DJ software including Serato Scratch Live, Traktor, Ableton Live
- All MIDI control elements can be edited and freely assigned
- ASIO drivers with minimum latency and high-quality audio characteristics available for download (PC)
- The device can be connected via USB to the PC in connection with Virtual DJ<BR>midi capable

#### OMNITRONIC DD-5220L Turntable bk

Direct drive DJ turntable "Ultra Torque" with switchable phono/line output

- Direct drive high-torque motor Quartz-controlled for highest speed precision
- 3 speeds (33 1/3, 45 and 78 RPM), pitch control  $\pm 10\%$ ,  $\pm 20\%$ ,  $\pm 50\%$
- Selectable quartz-controlled pitch lock
- Quick start
- Adjustable start/stop time
- 2 large start/pause buttons
- Reverse run
- Plug-in LED target lamp
- Adjustable anti-skating
- Tone arm height adjustable
- Shock-absorbing and adjustable feet
- Switchable phono/line output
- Extremely resonance-free due to optimally combined components
- Platter and motor are directly connected for highest stability
- Recessed connections for easy case mounting
- Delivery includes headshell, slipmat and RCA cable
- Dust cover and pick-up system optionally available
- Impostazione del passo:  $\pm 10\%$ ,  $\pm 20\%$ ,  $\pm 50\%$

##### Dotazione della fornitura

- 1 x Dispositivo, 1 x Cavo di rete/Cavo di alimentazione, 1 x Piatti per fonografi, 1 x Tappetino in feltro, 1 x set Shell, 1 x Masse di equilibratura, 1 x connettore, 1 x adattatore, 1 x cavo RCA, 1 x Manuale d'uso

#### Dati tecnici :

---

Peso: 26,50 kg

---

#### OMNITRONIC CMX-2000 2+1-channel MIDI controller

Alimentazione elettrica: 100-240 V AC, 50/60 Hz

---

Potenza totale installata: 14 W

---

|                          |                                                                                                                                                        |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Allacciamento elettrico: | Alimentazione dell'energia elettrica tramite dispositivi a freddo (M) versione da incasso cavo di alimentazione con spina di protezione (in dotazione) |
| Collegamento USB:        | USB 2.0, type B                                                                                                                                        |
| PC connect:              | Virtual DJ via USB<br>Midi capable                                                                                                                     |
| Misure:                  | Larghezza: 36 cm<br>Profondità: 26,5 cm<br>Altezza: 10,5 cm                                                                                            |
| Peso:                    | 3,90 kg                                                                                                                                                |
| Inputs:                  |                                                                                                                                                        |
| Line:                    | 2 x stereo RCA                                                                                                                                         |
| Line/phono:              | 2 x stereo RCA, switchable                                                                                                                             |
| DJ microphone:           | combination XLR/6.3 mm jack, bal.                                                                                                                      |
| Aux:                     | 3.5 mm jack and stereo RCA                                                                                                                             |
| Outputs:                 |                                                                                                                                                        |
| Master:                  | XLR L/R and stereo RCA                                                                                                                                 |
| Booth:                   | stereo RCA                                                                                                                                             |
| Headphones output:       | 3.5 mm and 6.3 mm jack                                                                                                                                 |
| Converter:               | 16 bits                                                                                                                                                |
| Sample rate:             | 48 kHz                                                                                                                                                 |
| Faderstart:              | 2 x 3.5 mm jack                                                                                                                                        |

#### OMNITRONIC DD-5220L Turntable bk

|                            |                                                                                                                                                                                 |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Alimentazione elettrica:   | 230 V AC, 50 Hz                                                                                                                                                                 |
| Potenza totale installata: | 15,00 W                                                                                                                                                                         |
| Classe di protezione:      | CL I                                                                                                                                                                            |
| Allacciamento elettrico:   | Pavimento cavo di alimentazione con spina europea                                                                                                                               |
| Intervallo di frequenza:   | 20 - 20000 Hz                                                                                                                                                                   |
| Tipo di trazione:          | Quarz-controlled direct drive<br>Motore brushless a corrente continua                                                                                                           |
| Azionamento:               | Coppia di avviamento: 4,5 kg/cm<br>Tempo di avviamento: 0.2 - 6 sec, adjustable<br>Tempo di decelerazione: 0.2 - 6 sec, adjustable<br>Transizione di velocità: <1s 1kHz 5cm/sec |
| Flutter:                   | <0,1 % WRMS                                                                                                                                                                     |
| Rombo:                     | 60 dB DIN B                                                                                                                                                                     |
| Regime:                    | 33 Giri/min; 45 Giri/min; 78 Giri/min<br>avanti/indietro                                                                                                                        |
| Braccio di riproduzione:   | A forma di S con sospensione cardanica<br>Length: 230<br>Tonearm heigh: 8 - 10.5 mm adjustable<br>Overhang: 15 mm<br>Stylus pressure: 0-4 g, regolabile                         |
| Livello di uscita:         | Phono 1,5-3,6 mV/ 1 kHz 5 cm/sec<br>Line 90-216 mV/ 1 kHz 5 cm/sec                                                                                                              |

|                         |                                                             |
|-------------------------|-------------------------------------------------------------|
| Collegamenti:           | Uscita: line/phono via 1 x RCA stereo                       |
| Impostazione del passo: | ±10%, ±20%, ±50%                                            |
| Misure:                 | Larghezza: 45 cm<br>Profondità: 35,3 cm<br>Altezza: 15,6 cm |
| Peso:                   | 11,30 kg                                                    |
| Piatti per fonografi    |                                                             |
| Materiale:              | Metallo                                                     |
| Misure:                 | Diametro: Ø 33,2 cm                                         |
| Peso:                   | 1,425 kg                                                    |