

SOMMER CABLE SC-CICADA SO-D14 25m

Cavo di commutazione di alta qualità

Art.n.: 3030744Q

GTIN: 4026397424331



L'articolo non è più disponibile.

Features :

- Highly flexible due to the fine copper strand construction
- Easy to work with due to the additional filler strand (0.22 mm²)
- Outstanding shielding due to dense spiral shielding, 95 % optically opaque
- Longevity and resistant to notching due to the tough PUR-jacket

Logistica

EAN / GTIN: 4026397424331
Peso : 0,34 kg
Lunghezza : 0.25 m
Larghezza : 0.19 m
Altezza : 0.03 m

Dati tecnici :

Colore:	Nero
Construction:	(2LI2Y0,14 mm ²) DY
Jacket, diameter:	PUR Master Blend 2,6 mm
AWG:	26
No. of inner conductors:	2 x 0,14 mm ²
Copper strand per conductor:	18 x 0,10 mm
Cond. insulationCond. insulation:	PE 0,90 mm
Shielding:	copper spiral shielding + filler strand, tin-plated (0.22 mm ²)
Shielding factor:	95 %
Temperature range:	min. -30° C
Temperature range:	max. 70° C

Fire load per m:	0,08 kWh
Weight per 1 m:	13 g
Packaging:	25 m roll
ELECTRICAL DATA:	
Capac. cond./cond. per 1 m:	65 pF
Capac. cond./shield. per 1 m:	120 pF
Cond. resistance per 1 km:	<148 ohms
Shield. resistance per 1 km:	30 ohms
Insulation resist. per 1 km:	>1 Gohms