

EUROLITE ML-300 ABL Spot

Midsized spotlight with halogen lamp and LED ambient illumination

Art.n.: 41600005

GTIN: 4026397655513

L'articolo non è più disponibile.

Descrizione :

Effect spotlight with halogen lamp and LED ambient lighting

Use this effect spotlight on stages, events or presentations to achieve decorative light and show effects.

The EUROLITE ML-300 ABL Spot is a medium-sized spotlight with halogen lamp and LED ambient lighting. Under the grille cover, LEDs in red, green and blue are hidden to completely illuminate the large reflector. A 300 W GY 9.5 lamp, which is not included in the scope of delivery, is used in the middle.

When dimmed, the halogen lamp produces a wonderfully golden atmospheric light, but when fully extended it produces a bright, dazzling light.

Adjust the strobe effect speed and the dimmer brightness comfortably via DMX - also different dimmer curves are selectable. The strobe effect scores with 20 flashes per second. You can select 35 colors directly.

The spotlight is controlled via DMX, with master/slave function, in stand-alone mode or with the infrared remote control included in the scope of delivery. Addressing and settings can be made easily using the integrated control unit with LCD and the three control buttons.

With the Neutrik PowerCon mains connection and loop-through output, you can supply up to six devices with power.

Logistica

EAN / GTIN: 4026397655513

Peso : 8,25 kg

Lunghezza : 0.45 m

Larghezza : 0.48 m

Altezza : 0.43 m

Features :

- RGB LEDs are concealed under the mesh cover, in order to completely illuminate the large reflector with color
- When dimmed, the halogen lamp produces a wonderful, golden atmosphere light; when fully illuminated a bright, dazzling light
- Strobe effect with adjustable speed
- Various dimmer curves adjustable
- Mains input and output for power linking up to 8 units
- 18 potenti LED 0,2 W SMD 5050 3in1 TCL RGB
- Direct color selection for 35 preset colors
- Il dispositivo è raffreddato tramite Raffreddamento a convezione passiva
- Controllabile via stand-alone; Telecomando IR; DMX
- Già pre-programmato con Light´J; LED PC-Control 512; Light Captain
- Con staffa di montaggio
- Schermo LCD

Dotazione della fornitura

- 1 x Proiettori, 1 x Manuale d'uso, 1 x Cavo di rete/Cavo di alimentazione, 1 x telecomando, 1 x Pila

Dati tecnici :

Alimentazione elettrica:	230 V AC, 50 Hz
Potenza totale installata:	315 W
Grado di protezione:	IP20
Lampadina adatta:	230 V/300 W G-9.5
Potenza nominale:	300 W
Allacciamento elettrico:	Alimentazione dell'energia elettrica tramite PowerCON (blu), versione da incasso cavo di alimentazione con spina di protezione (in dotazione)
Uscita di corrente:	PowerCON (grigio)
Attacco/Porta lampada:	GY9.5
Tipo di lampada:	Lampada alogena
Tipo di LED:	18 x 0,2 W SMD 5050 3in1 TCL RGB
Frequenza di lampeggiamento:	0 - 20 Hz
Canali DMX:	1; 2; 4; 7
Ingresso DMX:	1 x XLR (M) a 3 poli versione da incasso 1 x Versione da incasso XLR (M) a 5 poli
Uscita DMX:	1 x XLR (F) a 3 poli versione da incasso 1 x Versione da incasso XLR (F) a 5 poli
Raffreddamento:	Raffreddamento a convezione passiva
Attivazione:	Stand-alone; Telecomando IR; DMX
Pre-programmato con:	Light´J; LED PC-Control 512; Light Captain
Colore della custodia:	Argento
Sistema di registrazione:	Staffa di montaggio
Tipo di display:	Schermo LCD
Misure:	Larghezza: 53 cm Profondità: 27,5 cm Altezza: 45,5 cm
Peso:	7,15 kg
Specifiche legali	

Prodotto speciale:	Non destinato all'illuminazione di ambienti domestici
Destinazione d'uso:	Illuminazione per effetti speciali