

## EUROLITE LED ML-56 COB RGB 100W Floor sil

ML spot with 100 W COB LED and RGB color mixing

Art.n.: 41607321

GTIN: 4026397588279



**L'articolo non è più disponibile.**

### Descrizione :

ML spot with 100 W COB LED and RGB color mixing

The Eurolite LED ML-56 spotlight is equipped with a 100 Watts Chip-on-Board (COB) LED in RGB colors, which ensure homogeneous color mixing. It is suitable for use in theatres, on large stages as a front spotlight and for mobile use. Because of the additional stand bracket, the ML-56 can also be used as a floor spot.

The effect spotlight comes with a variety of functions: Automatic color change, internal and user-defined programs, dimmer and strobe effect with variably adjustable speed. The flicker-free projection even makes it possible to use the spotlight for video recording.

You can control the Eurolite LED ML-56 COB via DMX with master/slave function or in standalone mode. In addition, the built-in microphone allows you to operate the spotlight via music control.

Comfortable addressing and setting is possible via the Control Board with four operating keys and LED display.

### Logistica

EAN / GTIN: 4026397588279

Peso : 4,00 kg

Lunghezza : 0.29 m

Larghezza : 0.29 m

Altezza : 0.39 m

### Features :

- Equipped with one COB 100 W LED in RGB colors
- Stepless color blend, color change, preset colors, dimmer and strobe effect
- Adjustable white balance
- Dimmer speed (step response) adjustable
- Stand-alone, master/slave and DMX mode
- Color presets can be called up via DMX controller
- Strobe effect with adjustable speed
- 40° beam angle

- Control panel with LED display for easy configuration
  - Additional bracket for floor use
  - 2 swivel mounting brackets
  - With color filter frame
  - Optional barndoors available
  - Ideal for theatres, large stages as pre-stage spot and mobile use
  - Various versions available
  - 1 potente LED 100 W COB (chip-on-board) 3in1 TCL RGB (miscela di colori omogenea)
  - Effetto stroboscopico
  - Il dispositivo è raffreddato tramite Ventola
  - Controllabile via DMX; controllo della musica via microfono
  - Già pre-programmato con EASY SHOW 1; Light´ J; LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
  - Senza sfarfallio
  - With a beam angle of 40°
- Dotazione della fornitura**
- 1 x telaio filtro

## Dati tecnici :

|                                                 |                                                                                                                                               |
|-------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| Alimentazione elettrica:                        | 100-240 V AC, 50/60 Hz                                                                                                                        |
| Potenza totale installata:                      | 90 W                                                                                                                                          |
| Grado di protezione:                            | IP20                                                                                                                                          |
| Classe di protezione:                           | CL I                                                                                                                                          |
| Allacciamento elettrico:                        | Pavimento cavo di alimentazione con spina di protezione                                                                                       |
| Lunghezza cavo:                                 | Circa 1,2 m                                                                                                                                   |
| Tipo di lampada:                                | Lampada a LED                                                                                                                                 |
| Tipo di LED:                                    | 1 x 100 W COB (chip-on-board) 3in1 TCL RGB (miscela di colori omogenea)                                                                       |
| Frequenza di lampeggiamento:                    | 0 - 17 Hz                                                                                                                                     |
| Canali DMX:                                     | 3; 3 (HSV hue/saturation/value); 5; 6; 9                                                                                                      |
| Ingresso DMX:                                   | 1 x XLR (M) a 3 poli versione da incasso                                                                                                      |
| Uscita DMX:                                     | 1 x XLR (F) a 3 poli versione da incasso                                                                                                      |
| Raffreddamento:                                 | Ventola                                                                                                                                       |
| Attivazione:                                    | DMX; controllo della musica via microfono                                                                                                     |
| Pre-programmato con:                            | EASY SHOW 1; Light´ J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain |
| Proiezione:                                     | Senza sfarfallio                                                                                                                              |
| Angolazione del fascio di luce:                 | 40°                                                                                                                                           |
| Angolazione del fascio di luce (1/2 picco):     | 40°                                                                                                                                           |
| Angolazione del fascio di luce (1/10 di picco): | 82°                                                                                                                                           |
| Colore della custodia:                          | Argento                                                                                                                                       |
| Misure:                                         | Larghezza: 31 cm<br>Profondità: 26 cm<br>Altezza: 30 cm                                                                                       |
| Peso:                                           | 3,41 kg                                                                                                                                       |
| Classificazione del rumore:                     | Classe 3 (rumori chiaramente percettibili)                                                                                                    |
| Specifiche legali                               |                                                                                                                                               |

|                     |                                                       |
|---------------------|-------------------------------------------------------|
| Prodotto speciale:  | Non destinato all'illuminazione di ambienti domestici |
| Destinazione d'uso: | Illuminazione per effetti speciali                    |