

EUROLITE AKKU UP-4 HCL Spot WDMX bk

LED Uplight with 4 x 12 W 6in1 LED & wireless DMX receiver (Wireless Solution)

Art.n.: 41700560

GTIN: 4026397539127



L'articolo non è più disponibile.

Features :

- Compact and bright
- Equipped with 4 x 12 W HCL (hexacolor LED) in red, green, blue, amber, white and UV
- With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
- Operation via mains connection or built-in rechargeable lithium-ion battery with up to 8.5 hours operating time
- Integrated automatic charging of the battery with indicator
- Controllable via EUROLITE IR-7 remote control; included in the delivery
- With integrated folding foot for angled placement by floor installation
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 6, 8 or 12 DMX channels selectable
- Functions: static colors, stepless RGBAW+UV color mixture, internal programs, dimmer, strobe effect with variable speed, sound-control
- Dimmer speed (step response) adjustable
- Adjustable microphone sensitivity
- Addressing via control panel with 4-digit LED display
- Switch-mode power supply for operation between 100 and 240 volts
- Ready for connection via included power cable with safety power plug
- Feed-through output allows to power up to 8 devices
- DMX control via any standard DMX controller
- Available in 2 housing colors: black and white
- Il dispositivo è raffreddato tramite Raffreddamento a convezione passiva
- Controllabile via stand-alone; W-DMX by wireless solution; Telecomando IR
- Già pre-programmato con Light´J; LED PC-Control 512; Light Captain
- Senza sfarfallio
- With a beam angle of 22°

Dispositivo

Logistica

EAN / GTIN: 4026397539127

Peso : 3,31 kg

Lunghezza : 0.22 m

Larghezza : 0.20 m

Altezza : 0.25 m

- Senza fili, flessibile e versatile
 - Durata di funzionamento fino a 8,5h a seconda del programma utilizzato
- Dotazione della fornitura**
- 1 x Dispositivo, 1 x telecomando

Dati tecnici :

Alimentazione elettrica:	100-240 V AC, 50/60 Hz
Potenza totale installata:	37 W
Grado di protezione:	IP20
Tipo di lampada:	Lampada a LED
Raffreddamento:	Raffreddamento a convezione passiva
Attivazione:	Stand-alone; W-DMX by wireless solution; Telecomando IR
Pre-programmato con:	Light´J; LED PC-Control 512; Light Captain
Proiezione:	Senza sfarfallio
Angolazione del fascio di luce:	22°
Angolazione del fascio di luce (1/2 picco):	22°
Angolazione del fascio di luce (1/10 di picco):	33°
Colore della custodia:	Nero
Misure:	Larghezza: 13,8 cm Profondità: 14,5 cm Altezza: 19,1 cm
Peso:	2,91 kg
Dispositivo	
Tipo di batteria:	1 x Ioni di litio 14,8 V, 6600 mAh, 97,68 Wh
Batteria:	Durata di funzionamento fino a 8,5h a seconda del programma utilizzato Tempo di ricarica 4,5h
Telecomando	
Pila:	1 x pila a bottone 3,0 V CR2025 litio-manganese montato
Battery pack type:	Li-ion 14.8 V, 6600 mAh (97.68 Wh)
Battery operation:	8.5 hours
Recharging time:	4.5 hours
Battery remote control:	CR2025 button cell 3 V
DMX channels:	6/8/12
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
Wireless signal transmission:	2.4 GHz (ISM)
LED type:	12 W HCL
LED number:	4
Beam angle:	22°
Dimensions (L x W x H):	145 x 138 x 191 mm
Specifiche legali	
Prodotto speciale:	Non destinato all'illuminazione di ambienti domestici

Destinazione d'uso:

Illuminazione per effetti speciali
