

EUROLITE LED Laser Slim FX Spot

Flat PAR spotlight with additional RG laser (2M) and strobe

Art.n.: 51741074

GTIN: 4026397620801



Features :

- 6 high-power 4 W 4in1 LEDs for RGBW wash effects
- 12 cold white 0.5 W SMD LEDs for fast, dynamic strobe effects
- 2 laser diodes project thousands of red and green laser beams
- Laser class 2M: does not require additional protective measures or appointment of a laser safety officer
- Spotlight, laser and strobe can be controlled individually
- Auto, music, master/slave and DMX mode
- Silent operation
- 7 built-in auto and music show programs
- Direct color selection for 20 preset colors
- Stepless color mixture, color change, color fade, dimmer and strobe effect
- Addressing and setting via control panel with 4-digit LED display
- Convenient wireless control via included IR remote control EUROLITE IR-7
- Sound-control via built-in microphone with adjustable microphone sensitivity
- DMX512 control possible via any commercial DMX controller
- 2, 3, 4, 6, 10, or 14 DMX channels selectable for various applications
- Swivel mounting bracket
- Additional bracket for floor use
- Feed-through output allows to power up to 8 devices
- 12 LED 0,5 W SMD 5050 bianco freddo (CW)
- 6 LED 4 W SMD 9080 4in1 QCL RGBW (miscela di colori omogenea)
- Effetto stroboscopico
- Laser class 2M
 does not require additional protective measures or appointment of a laser safety officer
- Il dispositivo è raffreddato tramite Ventola
- Controllabile via stand-alone; DMX; Telecomando IR; controllo della musica via microfono

Logistica

EAN / GTIN: 4026397620801

Peso : 2,07 kg

Lunghezza : 0.30 m

Larghezza : 0.28 m

Altezza : 0.16 m

- Fixtures disponibili per Light´J; LED PC-Control 512; Light Captain
- With a beam angle of 25°

Dati tecnici :

Alimentazione elettrica:	100-240 V AC, 50/60 Hz
Potenza totale installata:	60 W
Grado di protezione:	IP20
Allacciamento elettrico:	Alimentazione dell'energia elettrica tramite dispositivi a freddo (M) versione da incasso cavo di alimentazione con spina di protezione (in dotazione)
Uscita di corrente:	1 x dispositivi a freddo (F) versione da incasso
Tipo di lampada:	Lampada a LED
Tipo di LED:	12 x 0,5 W SMD 5050 bianco freddo (CW) 6 x 4 W SMD 9080 4in1 QCL RGBW (miscela di colori omogenea)
Frequenza di lampeggiamento:	0 - 20 Hz
Classe laser:	2M
Colore laser:	R/G
Modulo laser:	Verde (G) 50 mW 532nm Rosso (R) 100 mW 650nm
Canali DMX:	2; 3; 4; 6; 10; 14
Raffreddamento:	Ventola
Attivazione:	Stand-alone; DMX; Telecomando IR; controllo della musica via microfono
Fixtures disponibili per:	Light´J; LED PC-Control 512; Light Captain
Angolazione del fascio di luce (1/2 picco):	25°
Colore della custodia:	Nero
Misure:	Larghezza: 26,5 cm Profondità: 10 cm Altezza: 21 cm
Peso:	1,73 kg
Pila:	1 x pila a bottone 3,0 V CR2025 litio-manganese montato
LEDs	
Wash effect:	6 x RGBW (4in1), 4 W each
Strobe effect:	12 x white, 0.5 W each
DMX connection:	3-pin XLR
Prodotto speciale:	Non destinato all'illuminazione di ambienti domestici
Destinazione d'uso:	Illuminazione per effetti speciali

Contenuto della confezione:

1 x telecomando