

LASERWORLD DS-3000RGB ShowNET (2021)

Laser a diodi con interfaccia di rete ShowNET e software gratuito

Art.n.: 51743284

GTIN: 7640144997199



L'articolo non è più disponibile.

Features :

- Suitable for both beginners and professional users
- Upgrades of version 2021: new back plate with Interlock IN and THRU, Power IN and THRU, new push buttons for X/Y Invert and the other functions, revised key switch, faster galvos (40 kpps @8° ILDA) and 50° maximum deflection
- Multiple preset laser patterns included
- Integrated Scan Fail Safety
- Low-maintenance due to Sealed Housing Technology
- 2000 mW guaranteed power
- Graphics capable - 40 kpps@8° ILDA
- Max scan angle 45°
- Full colour mixing - analog modulation
- Extremely sharp intense beams - 4mm beam diameter and low divergence of 1.1mrad
- Save safety settings direct to the laser and they apply in all modes
- Link multiple units with linking Power, DMX and ILDA
- Integrated ShowNET network interface with free laser control software included
- Start with your own professional laser show thanks to the intuitive Showeditor laser show software
- The Showcontroller software is supported as well and can be purchased additionally
- The integrated ShowNET allows for direct input through ILDA and LAN. Besides DMX, it is possible to trigger single frames via ArtNET. Custom frames and shows can be played back from an integrated SD card (included in delivery) - even in sound-to-light and stand-alone mode.
- Il dispositivo è raffreddato tramite Ventola
- Controllabile via DMX; stand-alone; controllo della musica via microfono; ILDA

Dotazione della fornitura

- 1 x Laser, 1 x Manuale d'uso, 1 x Cavo di rete/Cavo di alimentazione, 2 x Chiave, 1 x Interlock, 2 x vite a testa zigrinata, 4 x Rondella, 1 x borsa

Logistica

EAN / GTIN: 7640144997199

Peso : 5,95 kg

Lunghezza : 0.31 m

Larghezza : 0.29 m

Altezza : 0.21 m

Dati tecnici :

Alimentazione elettrica:	100-240 V AC, 50/60 Hz
Potenza totale installata:	80 W
Grado di protezione:	IP20
Allacciamento elettrico:	Alimentazione dell'energia elettrica tramite P-Con (blu), versione da incasso cavo di alimentazione con spina di protezione (in dotazione)
Uscita di corrente:	1 x P-Con (grigio), versione da incasso
Classe laser:	4
Colore laser:	R/G/B
Modulo laser:	Rosso (R) 650 mW 638nm Verde (G) 900 mW 520nm Blu (B) 1600 mW 450nm
Raffreddamento:	Ventola
Attivazione:	DMX; stand-alone; controllo della musica via microfono; ILDA
Colore della custodia:	Nero
Misure:	Lunghezza: 21 cm Larghezza: 17 cm Altezza: 14,5 cm
Peso:	5,27 kg