

FUTURELIGHT PHS-280 PRO-Head-Spot

Brilliant multi-function moving head

Art.n.: 51838206

GTIN: 4026397395365



Features :

- Color-wheel with 7 different, dichroic color-filters and white and additionally with UV-filter
- Switchable color change (mode 1: only full colors, mode 2: color-change at every position)
- Rainbow effect with adjustable speed in both directions
- Gobo-wheel with 7 static metal gobos plus open
- Gobo-wheel with 7 rotating gobos plus open
- Slot-in gobo-system for exchanging gobos without tools
- With gobo-shake function
- Rotating 3-facet prism
- Macro-function for rotating gobos/rotating prism combinations
- Steplessly adjustable iris
- Motorized focus
- Different radiation angles (from approx. 18° to approx. 21°) possible via additional lens (included with delivery)
- Blue LCD-display
- Strobe effect with 1-13 flashes per second
- Random strobe effect
- Stepless frost-filter for fading the projections in or out
- Mechanic dimmer
- Exact positioning via 16 bit Pan/Tilt movement resolution
- Control-Board with LCD-display and foil-keyboard for adjusting the DMX-starting address, PAN/TILT-Reverse, Program, Reset, lamp on/off, operating hours
- RDMX (Remote DMX Addressing): DMX address setting via controller
- PAN-angle switchable between 630° and 540°
- DMX-controlled operation or stand-alone operation with master/slave function
- 56 preprogrammed scenes in Program Run for stand alone operation
- Number of scenes in Program Run can be changed individually

Logistica

EAN / GTIN: 4026397395365

Peso : 29,10 kg

Lunghezza : 0.59 m

Larghezza : 0.46 m

Altezza : 0.51 m

- The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
- 7 built-in programs can be called up via DMX-controller
- Software-upload by optional accessory via DMX link
- Sound-controlled via built-in microphone
- For MSD/HSD 250 or MSD 250/2 lamp
- DMX-control via every standard DMX-controller
- Per maggiori informazioni su questo prodotto, consultare "Download" nella scheda tecnica

Dati tecnici :

| | |
|-------------------------------------|---|
| Alimentazione elettrica: | 230 V AC, 50 Hz |
| Potenza totale installata: | 500,00 W |
| Peso: | 26,45 kg |
| DMX channels: | 16 |
| DMX connection: | 5-pin and 3-pin XLR |
| Flash-rate: | 13 Hz |
| Color wheel: | 7 dichroic plus white, UV-filter |
| Static gobo wheel: | 7 gobos and open |
| Rotating gobo wheel: | 7 gobos and open |
| Outside diameter of the gobos: | 27 mm |
| Image diameter of the gobos: | 23 mm |
| Maximum PAN-movement 630°: | in 2.5 s |
| Maximum TILT-movement 265°: | in 1.5 s |
| Beam angle: | 18° |
| Length of base (including handles): | 350 mm |
| Width of yoke: | 420 mm |
| Height (head horizontal): | 500 mm |
| Prodotto speciale: | Non destinato all'illuminazione di ambienti domestici |
| Destinazione d'uso: | Illuminazione per effetti speciali |

Contenuto della confezione: