

FUTURELIGHT PHW-280 PRO-Head-Wash

Multifunctional Washlight

Art.n.: 51838711

GTIN: 4026397395464



L'articolo non è più disponibile.

Features :

- Color-wheel with 5 different, dichroic color-filters and white and additionally with CTO and CTB correction-filters and UV-filter
- CMY color mixing
- Switchable color change (mode 1: only full colors, mode 2: color-change at every position)
- Rainbow effect with adjustable speed in both directions
- Macro-function for combinations between CMY color mixing and color-wheel
- Frost-filter for softer beam
- Beam-shape effect: wide and flat beam can steplessly be rotated by 180°
- Strobe effect with 1-13 flashes per second
- Random strobe effect
- Motorized zoom
- Mechanic dimmer
- Blue LCD display
- Exact positioning via 16 bit Pan/Tilt movement resolution
- DMX-controlled operation or stand alone operation with Master/Slave function
- 56 preprogrammed scenes in Program Run for stand alone operation
- Number of scenes in Program Run can be changed individually
- The scenes in Program Run can be modified via the control board or via an external controller and loaded into the memory
- 7 built-in programs can be called up via DMX-controller
- Control board with LCD display and foil-keyboard for adjusting the DMX-starting address, PAN/TILT-Reverse, Program, Reset, lamp on/off, operating hours
- PAN-angle switchable between 630° and 540°
- RDMX (Remote DMX Addressing): DMX address setting via controller
- Software-upload by optional FUTURELIGHT ULB-1 upload box via DMX link
- Sound-controlled via built-in microphone

Logistica

EAN / GTIN: 4026397395464

Peso : 28,50 kg

Lunghezza : 0.59 m

Larghezza : 0.46 m

Altezza : 0.50 m

- For MSD/HSD 250 or MSD 250/2 lamp
- DMX-control via every standard DMX controller

Dati tecnici :

Alimentazione elettrica:	230 V AC, 50 Hz
Potenza totale installata:	500,00 W
DMX channels:	16
DMX connection:	5-pin and 3-pin XLR
Flash-rate:	13 Hz
Color-wheel:	5 dichroic plus white, CTO and CTB correction-filters, UV-filter
Maximum PAN-movement 630°:	in 2.5 s
Maximum TILT-movement 265°:	in 1.5 s
Length of base (including handles):	370 mm
Width of yoke:	420 mm
Height (head horizontal):	500 mm
Weight:	25 kg
Specifiche legali	
Prodotto speciale:	Non destinato all'illuminazione di ambienti domestici
Destinazione d'uso:	Illuminazione per effetti speciali