

FUTURELIGHT PHW-575 PRO-Head WASH

Multifunctional Washlight

Art.n.: 51838720

GTIN: 4026397316223



L'articolo non è più disponibile.

Features :

- Color-wheel with 5 different, dichroic color filters and white and additionally with UV-filter, correction-filters 3200 K and 5,600 K
- Switchable color change (mode 1: only full colors, mode 2: color-change at every position)
- Slot-in system for exchanging color filters without tools
- Colored LCD display
- Rainbow effect with adjustable speed in both directions
- CMY color mixing for indefinite color variations
- Macro-function for combinations between CMY color mixing and color-wheel
- Strobe effect with 1-13 flashes per second via shutter
- Random strobe effect
- Control board with LCD display and foil-keyboard for adjusting the DMX-starting address, Pan/Tilt reverse, Program, Reset, lamp on/off, operating hours
- Remotely switching of the lamp
- Built-in demo sequence
- Preprogrammed variable/random strobe and dimmer pulse effects
- Black-out while Head moving or CMY/color/beam shaping changing
- Remotely controllable speed of PAN /TILT movement for easy programming
- Remote reset function
- Motorized zoom
- Lightbeam with 13°-50° radiation angle
- Mechanic dimmer
- Exact positioning via 16 bit Pan/Tilt movement resolution
- PAN-angle switchable between 630° and 540°
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 56 preprogrammed scenes in Program Run for stand-alone operation
- Number of scenes in Program Run can be changed individually

Logistica

EAN / GTIN: 4026397316223

Peso : 39,40 kg

Lunghezza : 0.72 m

Larghezza : 0.46 m

Altezza : 0.55 m

Merci voluminose

- The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
- 7 built-in programs can be called up via DMX controller
- Sound-controlled via built-in microphone
- For MSR 575SA/2 DE GOLD lamp
- DMX control via every standard DMX controller

Dati tecnici :

Alimentazione elettrica:	230 V AC, 50 Hz
Potenza totale installata:	850,00 W
DMX channels:	15
DMX connection:	5-pin and 3-pin XLR
Flash-rate:	13 Hz
Color-system:	CMY color-mixture
Color-wheel:	5 dichroic + white, UV-filter, 2 correction filters
Maximum PAN-movement 630°:	in 3.5 s
Maximum TILT-movement 265°:	in 2.5 s
Length of base (including handles):	470 mm
Width of yoke:	350 mm
Height (head horizontal):	520 mm
Weight:	34 kg
Specifiche legali	
Prodotto speciale:	Non destinato all'illuminazione di ambienti domestici
Destinazione d'uso:	Illuminazione per effetti speciali