

FUTURELIGHT EYE-15 CW/WW Zoom LED Moving Head Wash

3in1 moving head wash with zoom

Art.n.: 51841312

GTIN: 4026397503067



L'articolo non è più disponibile.

Features :

- Equipped with 15 x 10 W bicolor LED in cold and warm white
- With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
- Compact housing
- 13, 20 or 21 DMX channels selectable
- Exact positioning via 16 bit PAN/TILT movement resolution
- 5 LED segments independently controllable (3 LEDs x 5 segments)
- Master dimmer
- Motorized zoom with 22-45° beam angle
- Color presets
- Stepless CW/WW color mixture
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 540° and 630°
- Sound-controlled via built-in microphone
- Switch-mode power supply, automatic power supply adaption between 100 and 240 Volts without power selector
- Control board with graphic LCD display and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset
- DMX-controlled operation or stand-alone operation with Master/Slave function
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device

Logistica

EAN / GTIN: 4026397503067

Peso : 13,45 kg

Lunghezza : 0.48 m

Larghezza : 0.44 m

Altezza : 0.36 m

- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller
- Il dispositivo è raffreddato tramite ventola termoregolata
- Controllabile via DMX; stand-alone; RDM
- Già pre-programmato con LED PC-Control 512

Dati tecnici :

Alimentazione elettrica:	100-240 V AC, 50/60 Hz
Potenza totale installata:	280,00 W
Grado di protezione:	IP20
Tipo di lampada:	Lampada a LED
Raffreddamento:	Ventola termoregolata
Attivazione:	DMX; stand-alone; RDM
Pre-programmato con:	LED PC-Control 512
Angolazione del fascio di luce (1/2 picco):	22 - 45°
Colore della custodia:	Nero
Misure:	Larghezza: 25 cm Profondità: 34,4 cm Altezza: 44,5 cm
Peso:	12,10 kg
DMX channels:	13/20/21
DMX connection:	5-pin and 3-pin XLR
Sound-control:	via built-in microphone
Wireless signal transmission:	2.4 GHz (ISM)
Flash-rate:	18 Hz
LED number:	15
LED type:	10 W BCL
Beam angle:	22-45°
Maximum PAN-movement:	630°
Maximum TILT-movement:	270°
Dimensions (L x W x H):	250 x 344 x 445 mm
Specifiche legali	
Prodotto speciale:	Non destinato all'illuminazione di ambienti domestici
Destinazione d'uso:	Illuminazione per effetti speciali