

FUTURELIGHT Stage Pixel Bar 10

Bar with narrow beam 10 x 15 W RGBW LED and frost plate

Art.n.: 51841359

GTIN: 4026397561098



Features :

- Equipped with 10 high-power 4in1 LEDs in the colors red, green, blue and white
- Particularly bright illuminating power of the LEDs
- Collimator lenses for homogeneous beams with 4° beam angle
- Removable frost filter
- 4, 6, 8, 40 or 44 DMX channels selectable
- Each LED can be controlled individually
- Quick and easy control via Art-Net
- For use via appropriate lighting control software supporting Art-Net
- Programmable color change speed, strobe effect and dimmer
- Dimmer speed (step response) adjustable
- Strobe effect with 1-18 flashes per second
- RGBW color mixing
- Static colors
- Internal programs
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Manual, sound, DMX- or ArtNet-controlled operation
- Sound-control via built-in microphone; adjustable sensitivity
- For large stage backgrounds in public places, main halls and lounges
- Hanging as well as standing installation possible
- Locking possibility at the mounting bracket
- Addressing via control panel with LCD screen and four operating buttons
- EtherCon input and output
- Switch-mode power supply for operation between 100 and 240 volts
- Power connection via Neutrik PowerCon jack and included power cable with safety plug
- Feed-through output allows to power up to 8 devices
- DMX control via any standard DMX controller

Logistica

EAN / GTIN: 4026397561098

Peso : 11,60 kg

Lunghezza : 0.97 m

Larghezza : 0.24 m

Altezza : 0.27 m

- 10 LED 15 W high power 4in1 RGBW (miscela di colori omogenea)
- Effetto stroboscopico
- Controllabile via Art-Net; stand-alone; DMX; controllo della musica via microfono; RDM
- Fixtures disponibili per Light´J; LED PC-Control 512; EASY SHOW 1
- Senza sfarfallio
- With a beam angle of 4°

Dati tecnici :

Alimentazione elettrica:	100-240 V AC, 50/60 Hz
Potenza totale installata:	170 W
Allacciamento elettrico:	Alimentazione dell'energia elettrica tramite PowerCON (blu), versione da incasso cavo di alimentazione con spina di protezione (in dotazione)
Uscita di corrente:	1 x PowerCON (grigio), versione da incasso
Tipo di lampada:	Lampada a LED
Tipo di LED:	10 x 15 W high power 4in1 RGBW (miscela di colori omogenea)
Frequenza di lampeggiamento:	0 - 18 Hz
Canali DMX:	4; 6; 8; 40; 44
Attivazione:	Art-Net; stand-alone; DMX; controllo della musica via microfono; RDM
Fixtures disponibili per:	Light´J; LED PC-Control 512; EASY SHOW 1
Proiezione:	Senza sfarfallio
Angolazione del fascio di luce (1/2 picco):	4°
Angolazione del fascio di luce (1/10 di picco):	7°
Colore della custodia:	Nero
Misure:	Lunghezza: 88 cm Profondità: 15,9 cm Altezza: 17,8 cm
Peso:	9,70 kg
Protocol:	Art-Net 3
Signal port:	2 x RJ45 (EtherCon)
DMX connection:	5-pin and 3-pin XLR
Prodotto speciale:	Non destinato all'illuminazione di ambienti domestici
Destinazione d'uso:	Illuminazione per effetti speciali

Contenuto della confezione: