

FUTURELIGHT LB-648 LED Bar SMD 5050

PRO TCL bar with 110° beam angle

Art.n.: 51841373

GTIN: 4026397474701



L'articolo non è più disponibile.

Features :

- Equipped with 648 tricolor LEDs (81 LEDs x 8 segments)
- 8 LED segments independently controllable
- 3, 5, 7 or 24 DMX channels selectable for numerous applications
- Mounting bracket for installation on a truss system included
- Functions: static colors, RGB color change, internal programs, dimmer, Master/Slave
- Programmable color change speed
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Strobe effect with 1-30 flashes per second
- Sound-controlled via built-in microphone
- Microphone-sensitivity adjustable via rotary-control
- Comfortable addressing and setting via Control Board with LED display and four operating buttons with 14 segment display
- Feed-through output allows to power another device
- After every 6 devices the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller

Logistica

EAN / GTIN: 4026397474701

Peso : 6,60 kg

Lunghezza : 0.86 m

Larghezza : 0.20 m

Altezza : 0.23 m

Dati tecnici :

Alimentazione elettrica: 100-240 V AC, 50/60 Hz

Potenza totale installata: 150,00 W

Misure: Larghezza: 80,3 cm

Profondità: 12,1 cm

Altezza: 17,8 cm

Peso:	5,50 kg
DMX channels:	3/5/7/24
DMX connection:	5-pin and 3-pin XLR
Flash-rate:	1-30 Hz
Sound-control:	via built-in microphone
Beam angle:	110°
LED number:	648
LED type:	TCL, SMD 5050
Dimensions (W x D x H):	803 x 121 x 178 mm
Specifiche legali	
Prodotto speciale:	Non destinato all'illuminazione di ambienti domestici
Destinazione d'uso:	Illuminazione per effetti speciali