

FUTURELIGHT DMH-90 LED Moving Head

High performance LED moving head with LUMINUS CBM-360 LED

Art.n.: 51841950

GTIN: 4026397461633



L'articolo non è più disponibile.

Features :

- 1 extra bright LUMINUS CBM-360 LED for best luminance
- 16, 18 or 19 DMX channels selectable
- Effect wheel with rotating 3-facet prism and 8-facet prism and frost filter
- Color wheel with 8 different dichroic color filters plus white
- Rainbow effect with adjustable speed in both directions
- Gobo wheel with 7 rotating gobos plus open
- All gobos can be interchanged
- Slot-in gobo system for exchanging gobos without tools
- With gobo shake function
- Exact positioning via 16 bit PAN/TILT movement resolution
- Motorized focus
- Dimmer
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 540° and 630°
- Sound-controlled via built-in microphone
- Switch-mode power supply
- Automatic power supply adaption between 100 and 240 Volts without power selector
- Control board with graphic LCD display and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset
- DMX-controlled operation or stand-alone operation with Master/Slave function
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link

Logistica

EAN / GTIN: 4026397461633

Peso : 16,00 kg

Lunghezza : 0.56 m

Larghezza : 0.43 m

Altezza : 0.35 m

- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via any standard DMX controller
- Controllabile via controllo della musica via microfono; DMX; RDM

Dati tecnici :

Alimentazione elettrica:	100-240 V AC, 50/60 Hz
Potenza totale installata:	200 W
Movimento oscillatorio TILT massimo:	270° posizionamento
Movimento di rotazione PAN massimo:	630° posizionamento
Gobo:	Diametro esterno 27mm Diametro immagine 22mm
Canali DMX:	16; 18; 19
Attivazione:	Controllo della musica via microfono; DMX; RDM
Angolazione del fascio di luce (1/2 picco):	14°
Colore:	Nero
Misure:	Larghezza: 34,3 cm Profondità: 25 cm Altezza: 42,8 cm
Peso:	13,70 kg
DMX channels:	16/18/19
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
LED type:	LUMINUS CBM-360
LED number:	1
Beam angle:	14°
Color-wheel:	8 dichroic filters plus open
Rotating gobo-wheel:	7 gobos and open
Outside diameter of the gobos:	27 mm
Image diameter of the gobos:	22 mm
Maximum PAN-movement:	630°
Maximum TILT-movement:	270°
Dimensions (L x W x H):	343 x 250 x 428 mm
Specifiche legali	
Prodotto speciale:	Non destinato all'illuminazione di ambienti domestici
Destinazione d'uso:	Illuminazione per effetti speciali