

EUROLITE LED PAR-56 RGB 5mm Short 5CH sil

PAR-56 spot with 151 LEDs in the colors red, green and blue

Art.n.: 51913618

GTIN: 4026397403497



L'articolo non è più disponibile.

Features :

- Equipped with 151 x 5 mm LED: 51 x red, 49 x green, 51 x blue
- Operable in stand-alone mode or with DMX interface
- DMX-512 control possible via any commercial DMX-controller (occupies 5 channels)
- 3 or 5 DMX channels selectable for numerous applications
- Sound-control via built-in microphone
- Adjustable microphone sensitivity via LED display
- Comfortable addressing and setting via control panel with LED display and three operating buttons
- Functions: static colors; RGB color blend, internal programs, dimmer and strobe settings via DMX; master/slave
- Housing available in silver or in black
- Locking possibility at the mounting bracket
- Ready for connection with power cord and safety plug
- 151 potenti LED 5 mm R/G/B (miscela di colori omogenea)
- Effetto stroboscopico
- Controllabile via stand-alone; DMX; controllo della musica via microfono
- Già pre-programmato con Light J; LED PC-Control 512
- With a beam angle of 21°

Logistica

EAN / GTIN: 4026397403497

Peso : 1,60 kg

Lunghezza : 0.21 m

Larghezza : 0.21 m

Altezza : 0.27 m

Dati tecnici :

Alimentazione elettrica: 230 V AC, 50 Hz

Potenza totale installata: 23 W

Grado di protezione: IP20

Allacciamento elettrico:	Pavimento cavo di alimentazione con spina di protezione
Tipo di lampada:	Lampada a LED
Tipo di LED:	151 x 5 mm R/G/B (miscela di colori omogenea)
Canali DMX:	5; 3
Ingresso DMX:	1 x XLR (M) a 3 poli versione da incasso
Uscita DMX:	1 x XLR (F) a 3 poli versione da incasso
Attivazione:	Stand-alone; DMX; controllo della musica via microfono
Pre-programmato con:	Light´J; LED PC-Control 512
Angolazione del fascio di luce:	21°
Angolazione del fascio di luce (1/2 picco):	21°
Colore della custodia:	Argento
Misure:	Larghezza: 20,5 cm Profondità: 16,5 cm Altezza: 24 cm
Peso:	1,45 kg
Specifiche legali	
Prodotto speciale:	Non destinato all'illuminazione di ambienti domestici
Destinazione d'uso:	Illuminazione per effetti speciali