

EUROLITE LED FLD-252 6000K 10mm Flood

Compact LED floodlight

Art.n.: 51913865

GTIN: 4026397304626



L'articolo non è più disponibile.

Descrizione :

Say hallo to Mr. Bright!

Difference is everywhere. All wines are not created equal, such are cellphones or is bright light. Concerning the light, this can be demonstrated with our new LED floodlight. As the 252 LEDs know their business, they produce a brightness that has no equal. Whether it is used on stages, at public places or in clubs, our compact floodlight always wins you over. By the way, you can easily adjust the dimmer and strobe functions and via a built-in microphone the movements are sound-controlled. But on account of the ultra bright lights, we recommend to wear sunglasses.

Logistica

EAN / GTIN: 4026397304626

Peso : 4,50 kg

Lunghezza : 0.54 m

Larghezza : 0.23 m

Altezza : 0.21 m

Features :

- Ultra bright white LEDs, 6000 K
- DMX512 control via regular DMX controller (occupies 2 channels)
- Sound-control via built-in microphone
- Adjustable Dimmer and Strobe functions
- Master/Slave function
- Rugged compact housing in a beautiful design
- Ideal for bands, stages or solo entertainers
- Perfect in public places, main halls, lounges
- Mounting bracket for installation on a truss system included
- Advantages of LED technology: long life of the LEDs, low power consumption, minimal heat emission, defacto maintenance free with brilliant light radiation
- Controllabile via stand-alone; DMX; controllo della musica via microfono
- Già pre-programmato con Light´J

Dati tecnici :

Alimentazione elettrica:	230 V AC, 50 Hz
Potenza totale installata:	20 W
Grado di protezione:	IP20
Tipo di lampada:	Lampada a LED
Canali DMX:	2
Attivazione:	Stand-alone; DMX; controllo della musica via microfono
Pre-programmato con:	Light´J
Angolazione del fascio di luce (1/2 picco):	30°
Colore della custodia:	Nero
Misure:	Larghezza: 45,5 cm Profondità: 12,5 cm Altezza: 24 cm
Peso:	4,05 kg
DMX channels:	2
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
LED number:	252
Beam angle:	30°
Color temperature:	6000 K
Dimensions (L x W x H):	125 x 455 x 240 mm
Specifiche legali	
Prodotto speciale:	Non destinato all'illuminazione di ambienti domestici
Destinazione d'uso:	Illuminazione per effetti speciali