EUROLITE LED PAR-64 HCL Hypno floor bl

PAR spot with 7 x 12 W 6in1 LED (RGBAW&UV) and 3 RGB hypno rings

Art.n.: 51914024

GTIN: 4026397621914

L'articolo non è più disponibile.

Features :

- 7 high-power 12 W 6in1 LEDs for RGBAW color mixing and blacklight
- 3 concentric hypno rings with altogether 120 RGB LEDs provide fast, dynamic ring effects
- Individual control of center RGBAW+UV LEDs and each RGB ring for spectacular animations
- Built-in auto and music show programs
- Direct color selection for 20 preset colors
- Stepless color blend, color change, color fade, dimmer and strobe effect
- Addressing and setting via control panel with 4-digit LED display
- Convenient wireless control via included IR remote control EUROLITE IR-7
- Swivel mounting bracket
- Additional bracket for floor use
- IEC terminals for power linking up to 8 units
- Silver or black housing available
- 120 potenti LED 0,5 W SMD 5050 3in1 TCL RGB (miscela di colori omogenea)
- 7 potenti LED 12 W high power 6in1 HCL RGBWA/UV (miscela di colori omogenea)
- Effetto stroboscopico; Effetto UV
- Controllabile via stand-alone; DMX; Telecomando IR; controllo della musica via microfono; funzione master/slave
- Già pre-programmato con Light´J; LED PC-Control 512
- Senza sfarfallio
- With a beam angle of 23°

Dotazione della fornitura

- 1 x telecomando

Logistica

EAN / GTIN: 4026397621914
Peso : 3,22 kg
Lunghezza : 0.25 m
Larghezza : 0.25 m
Altezza : 0.39 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® und Dimavery® sind Marken der Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Alle Rechte vorbehalten.Technische Änderungen und Irrtum vorbehalten. Alle Bilder ähnlich, zum Teil Symbolfotos.

Dati tecnici :

Alimentazione elettrica:	100-240 V AC, 50/60 Hz
Potenza totale installata:	75 W
Grado di protezione:	IP20
Allacciamento elettrico:	Alimentazione dell'energia elettrica tramite dispositivi a freddo (M) versione da incasso cavo di alimentazione con spina di protezione (in dotazione)
Uscita di corrente:	1 x dispositivi a freddo (F) versione da incasso
Tipo di lampada:	Lampada a LED
Tipo di LED:	120 x 0,5 W SMD 5050 3in1 TCL RGB (miscela di colori omogenea) 7 x 12 W high power 6in1 HCL RGBWA/UV (miscela di colori omogenea)
Frequenza di lampeggiamento:	0 - 20 Hz
Canali DMX:	3; 6; 7; 24
Ingresso DMX:	1 x XLR (M) a 3 poli versione da incasso
Uscita DMX:	1 x XLR (F) a 3 poli versione da incasso
Attivazione:	Stand-alone; DMX; Telecomando IR; controllo della musica via microfono; funzione master/slave
Pre-programmato con:	Light´J; LED PC-Control 512
Proiezione:	Senza sfarfallio
Angolazione del fascio di luce:	23°
Angolazione del fascio di luce (1/2 picco):	23°
Angolazione del fascio di luce (1/10 di picco):	41°
Colore della custodia:	Nero
Misure:	Larghezza: 29,6 cm Profondità: 35,8 cm Altezza: 22 cm
Peso:	2,68 kg
Fattore di rischio fotobiologico:	Gruppo di rischio 0
Telecomando	
Pila:	1 x pila a bottone 3,0 V CR2025 litio-manganese montato
Specifiche legali	
Prodotto speciale:	Non destinato all'illuminazione di ambienti domestici
Destinazione d'uso:	Illuminazione per effetti speciali

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® und Dimavery® sind Marken der Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Alle Rechte vorbehalten.Technische Änderungen und Irrtum vorbehalten. Alle Bilder ähnlich, zum Teil Symbolfotos.