

## EUROLITE LED IP CCR-600 QCL Wall Light incl. Flight Case

PRO outdoor spotlight (IP65) in case with 60 x 8 W 4in1 LED (RGBW)

Art.n.: 51914133

GTIN: 4026397573169



**L'articolo non è più disponibile.**

### Features :

- DMX-controlled operation or stand-alone operation with Master/Slave function
- DMX control via any standard DMX controller
- 4, 5, or 8 DMX channels selectable
- With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
- For architectural lighting
- Suitable for external use (IP65)
- For permanent installation
- Equipped with 60 x 4in1 QCL LED in the colors red, green, blue and white
- Stepless RGBW color blend
- Color macros
- Dimmer
- Dimmer speed (step response) adjustable
- Strobe effect with adjustable speed
- Internal programs
- Programmable color change speed
- Addressing and setting via Control Board with LED display and four operating buttons
- Switch-mode power supply for operation between 100 and 240 volts
- Feed-through output allows to power up to 8 devices
- Ready for connection via power cord with 3-pin 16A CEE plug
- Flightcase included in delivery
- Il dispositivo è raffreddato tramite Raffreddamento a convezione passiva
- Controllabile via stand-alone; DMX; W-DMX by wireless solution
- Già pre-programmato con Light 'J'; LED PC-Control 512
- Senza sfarfallio
- With a beam angle of 15°
- Adatto per uso esterno IP65

### Logistica

EAN / GTIN: 4026397573169

Peso : 35,40 kg

Lunghezza : 0.74 m

Larghezza : 0.34 m

Altezza : 0.56 m

Merci voluminose

## Dati tecnici :

Alimentazione elettrica:	100-240 V AC, 50/60 Hz
Potenza totale installata:	230 W
Grado di protezione:	IP65
Tipo di lampada:	Lampada a LED
Raffreddamento:	Raffreddamento a convezione passiva
Attivazione:	Stand-alone; DMX; W-DMX by wireless solution
Pre-programmato con:	Light'J; LED PC-Control 512
Proiezione:	Senza sfarfallio
Angolazione del fascio di luce:	15°
Angolazione del fascio di luce (1/2 picco):	15°
Angolazione del fascio di luce (1/10 di picco):	48°
Colore della custodia:	Nero
Misure:	Larghezza: 64 cm Profondità: 26,5 cm Altezza: 43 cm
Peso:	35,30 kg
Protection grade:	IP65
DMX channels:	4/5/8
DMX connection:	3-pin XLR
Beam angle:	15°
LED type:	8 W QCL (R,G,B,W)
LED number:	60
Flash-rate:	18 Hz
Dimensions (L x W x H):	640x265x430mm
Specifiche legali	
Prodotto speciale:	Non destinato all'illuminazione di ambienti domestici
Destinazione d'uso:	Illuminazione per effetti speciali