

EUROLITE LED IP PAD COB RGB 150W

Weather-proof DMX spotlight (IP65) with 150 W COB LED (RGB)

Art.n.: 51914166

GTIN: 4026397460827



L'articolo non è più disponibile.

Features :

- 3, 5 or 6 DMX channels selectable for numerous applications
 - Equipped with one 150 W COB RGB LED
 - For architectural lighting
 - Suitable for external use (IP65)
 - Compact, matt grey housing
 - Convection cooling via cooling ribs
 - Functions: Static colors, RGB color mixture, built-in programs, dimmer, strobe effect, Master/Slave operation
 - Programmable color change speed and strobe effect
 - DMX-controlled operation or stand-alone operation with Master/Slave function
 - Comfortable addressing and setting via Control Board with LC display and four operating buttons
 - Infrared remote control in credit card format included in delivery
 - Switch-mode power supply, automatic power supply adaption between 100 and 240 volts without power selector
 - Feed-through output allows to power another device
 - After every 8 devices the fixtures must have a renewed connection with the power mains
 - DMX512 control via any standard DMX-controller
 - Controllabile via stand-alone; Telecomando IR; DMX
 - Già pre-programmato con Light'J; LED PC-Control 512
 - Adatto per uso esterno IP65
- Dotazione della fornitura**
- 1 x telecomando

Logistica

EAN / GTIN: 4026397460827

Peso : 11,35 kg

Lunghezza : 0.38 m

Larghezza : 0.29 m

Altezza : 0.43 m

Dati tecnici :

Alimentazione elettrica:	100-240 V AC, 50/60 Hz
Potenza totale installata:	180 W
Grado di protezione:	IP65
Tipo di lampada:	Lampada a LED
Canali DMX:	3
Attivazione:	Stand-alone; Telecomando IR; DMX
Pre-programmato con:	Light´J; LED PC-Control 512
Angolazione del fascio di luce (1/2 picco):	60°
Colore della custodia:	Grigio
Misure:	Larghezza: 34,4 cm Profondità: 22 cm Altezza: 32,6 cm
Peso:	10,20 kg
Telecomando	
Pila:	1 x pila a bottone 3,0 V CR2025 litio-manganese montato
Protection grade:	IP65
DMX channels:	3/5/6
DMX connection:	3-pin screw connector
LED number:	1
LED type:	150 W COB RGB
Beam angle:	60°
Dimensions (L x W x H):	344 x 220 x 326 mm
Specifiche legali	
Prodotto speciale:	Non destinato all'illuminazione di ambienti domestici
Destinazione d'uso:	Illuminazione per effetti speciali