

EUROLITE LED IP PAR 36x1W RGB

Weather-proof DMX spotlight (IP65) with 36 x 1 W LED in red, green and blue

Art.n.: 51914174

GTIN: 4026397434842



L'articolo non è più disponibile.

Features :

- Equipped with 36 x 1 W LED: 12 x red, 12 x green and 12 x blue
 - 3 or 5 DMX channels selectable for numerous applications
 - Beam angle approximately 15°
 - Locking possibility at the mounting bracket
 - Ideal as floor spot via additional bracket
 - Stepless RGB color change
 - 7 color presets and 4 built-in programs
 - DMX-controlled operation or stand-alone operation with Master/Slave function
 - Dimmer and strobe settings via DMX
 - Suitable for external use (IP65)
 - Perfect for architectural lighting in public places and buildings
 - Addressing via control panel with 4-digit LED display
 - Control via control panel with display or any regular DMX controller
 - Feed-through output allows to power another device
 - After every 8 spot the fixtures must have a renewed connection with the power mains
 - 36 potenti LED 1 W high power R/G/B (miscela di colori omogenea)
 - Effetto stroboscopico
 - Il dispositivo è raffreddato tramite Raffreddamento a convezione passiva
 - Controllabile via stand-alone; DMX
 - Già pre-programmato con Light'J; LED PC-Control 512
 - With a beam angle of 15°
- Dotazione della fornitura**
- 1 x cavi adattatori

Logistica

EAN / GTIN: 4026397434842

Peso : 4,30 kg

Lunghezza : 0.27 m

Larghezza : 0.27 m

Altezza : 0.32 m

Dati tecnici :

Alimentazione elettrica:	230 V AC, 50 Hz
Potenza totale installata:	50 W
Grado di protezione:	IP65
Allacciamento elettrico:	Alimentazione dell'energia elettrica tramite connettore a vite a 3 poli (M) IP cavo di alimentazione con spina di protezione (in dotazione)
Uscita di corrente:	1 x connettore a vite a 3 poli (F) IP
Tipo di lampada:	Lampada a LED
Tipo di LED:	36 x 1 W high power R/G/B (miscela di colori omogenea)
Canali DMX:	3; 5
Ingresso DMX:	1 x connettore a vite a 3 poli (M) IP
Uscita DMX:	1 x connettore a vite a 3 poli (F) IP
Raffreddamento:	Raffreddamento a convezione passiva
Attivazione:	Stand-alone; DMX
Pre-programmato con:	Light´J; LED PC-Control 512
Angolazione del fascio di luce:	15°
Angolazione del fascio di luce (1/2 picco):	15°
Colore della custodia:	Nero
Misure:	Larghezza: 24 cm Profondità: 20 cm Altezza: 32 cm
Peso:	3,85 kg
Specifiche legali	
Prodotto speciale:	Non destinato all'illuminazione di ambienti domestici
Destinazione d'uso:	Illuminazione per effetti speciali