


ALUTRUS TRILOCK QTTR-4000 3-way cross beam

Sistema di traverse a 3 punti

Art.n.: 60301840

GTIN: 4026397092219



L'articolo non è più disponibile.

Descrizione :

TRILOCK QTTR 3-point truss system

TRILOCK QTTR is a 3-point truss system made of aluminum. The individual elements are connected via three cones, pivots and pins. The advantage of the conical connection system is that the cones completely fit into the main chords so that highest load capacity is guaranteed. The Quick-Lock system enables fast, efficient and highly aesthetic assembly when the truss constructions are frequently assembled and dismantled.

The three main chords are made of 50 mm aluminum tube with 2 mm wall thickness and offer a good relation between strength and weight. The braces have a diameter of 16 mm with 2 mm wall thickness and leave enough space for installing couplers, hooks and clamps. With 290 and 257 mm outer dimensions, TRILOCK QTTR is a stable truss system for higher loads and extended durability.

This system is mainly designed for intense use in stage installations, fair installations, event installations but also for permanent installations in discotheques and theatres. Its polished surface makes this universal system a real eyecatcher. Due to its wide range of standard system lengths, corners, circles and accessory, this system is highly versatile and offers unlimited design possibilities.

The production of this truss system is TUV-monitored. The load table as calculation base can be downloaded from the Internet before buying the product!

Features :

- High-quality aluminum-tubes with 50 mm in diameter
- Easy installation
- Low weight
- For exhibition and shop installers, discotheque and theatre installations

Logistica

EAN / GTIN: 4026397092219

Peso : 16,10 kg

Lunghezza : 4.00 m

Larghezza : 0.32 m

Altezza : 0.28 m

Merci voluminose

- Per maggiori informazioni su questo prodotto, consultare "Download" nella scheda tecnica

Dati tecnici :

| | |
|--------------------|--|
| Misure: | Lunghezza: 400 cm Larghezza: 29 cm Profondità: 29 cm |
| Main chords: | 50 x 2 mm |
| Braces: | 16 x 2 mm |
| Alloy: | AlMgSi 0.5 |
| Welding material: | AlMg 5 |
| Welding technique: | TIG-welding |
| Dimensions: | 240 mm (center - center) |
| Length: | 4000 mm |